

WHAT IS CLAIMED IS:

1. A transmission diversity detection circuit for notifying presence or absence of a transmission diversity of spread spectrum communication by modulation of SCH (Synchronization channel), comprising:

arithmetic means for calculating a calculated value of $C_{2n,0} \times S_{2n,0}^* + C_{2n,0}^* \times S_{2n,0} + C_{2n,1} \times C_{2n,1}^*$

in first and second symbols in a predetermined number of series of slots with respect to a reception signal, taking a primary CPICH (common pilot channel) symbol with respect to said first symbol as $C_{2n,0}$, a SCH symbol with respect to said first symbol as $S_{2n,0}$, a primary CPICH symbol with respect to said second symbol as $C_{2n,1}$ and a SCH symbol with respect to said second symbol as $S_{2n,1}$;

taking a complex conjugate of said primary CPICH symbol $C_{2n,0}$ as $C_{2n,0}^*$, a complex conjugate of SCH symbol $S_{2n,0}$ as $S_{2n,0}^*$, a complex conjugate of said primary CPICH symbol $C_{2n,1}$ as $C_{2n,1}^*$ and a complex conjugate of said SCH symbol ($S_{2n,1}$ as $S_{2n,1}^*$); and judgment means for making judgment whether transmission diversity is present or not depending upon positive or negative of said calculated value.

2. A transmission diversity detection circuit as set forth in claim 1, wherein said arithmetic means comprises:

circuits for deriving said complex conjugate $C_{2n,0}^*$ of said

00740975-12100
001221-5204200

Sub B1

primary CPICH symbol $C_{2n,0}$, a complex conjugate $S_{2n,0}^*$ of SCH symbol $S_{2n,0}$, a complex conjugate $C_{2n,1}^*$ of said primary CPICH symbol $C_{2n,1}$ and a complex conjugate $S_{2n,1}^*$ of said SCH symbol $S_{2n,1}$;

multipliers calculating $C_{2n,0} \times S_{2n,0}^*$, $C_{2n,0}^* \times S_{2n,0}$ and $C_{2n,1}^*$
5 $\times C_{2n,1}$; and

an adder calculating a sum of $C_{2n,0} \times S_{2n,0}^* + C_{2n,0}^* \times S_{2n,0}$
+ $C_{2n,1}^* \times C_{2n,1}$;

said judgment means makes judgment whether transmission
diversity is performed or not depending upon positive or negative
10 of sign of said sum.

3. A transmission diversity detection circuit as set forth
in claim 1, wherein said predetermined slot is even numbered
slots in one frame, said first and second symbols are (0)th
15 and first symbols of said slot.

4. A transmission diversity detection circuit as set forth
in claim 1, wherein said arithmetic means performs arithmetic
operation upon performing communication.

20

5. A transmission diversity detection circuit as set forth
in claim 1, wherein said arithmetic means performs arithmetic
operation upon registration of position for communication.

25 6. A transmission diversity detection method for notifying

007405 12100

presence or absence of a transmission diversity of spread spectrum communication by modulation of SCH (Synchronization channel), comprising:

calculating step for calculating a calculated value of
5 $C_{2n,0} \times S_{2n,0}^* + C_{2n,0}^* \times S_{2n,0} + C_{2n,1} \times C_{2n,1}^*$, in first and second symbols
in a predetermined number of series of slots with respect to
a reception signal, taking a primary CPICH (Common pilot channel)
symbol with respect to said first symbol as $C_{2n,0}$, a SCH symbol
with respect to said first symbol as $S_{2n,0}$, a primary CPICH symbol
10 with respect to said second symbol as $C_{2n,1}$ and a SCH symbol with
respect to said second symbol as $S_{2n,1}$, and taking a complex
conjugate of said primary CPICH symbol $C_{2n,0}$ as $C_{2n,0}^*$, a complex
conjugate of SCH symbol $S_{2n,0}$ as $S_{2n,0}^*$, a complex conjugate of
said primary CPICH symbol $C_{2n,1}$ as $C_{2n,1}^*$ and a complex conjugate
15 of said SCH symbol $S_{2n,1}$ as $S_{2n,1}^*$; and

judging step for making judgment whether transmission
diversity is present or not depending upon positive or negative
of said calculated value.

20 7. A transmission diversity detection method as set forth
in claim 6, wherein said calculating step comprises steps of:

deriving said complex conjugate $C_{2n,0}^*$ of said primary CPICH
symbol $C_{2n,0}$, a complex conjugate $S_{2n,0}^*$ of SCH symbol $S_{2n,0}$, a complex
conjugate $C_{2n,1}^*$ of said primary CPICH symbol $C_{2n,1}$ and a complex
25 conjugate $S_{2n,1}^*$ of said SCH symbol $S_{2n,1}$;

$C_{2n,1}$

8. A transmission diversity detection method as set forth
in claim 6, wherein said predetermined slot is even numbered
10 slots in one frame, said first and second symbols are (0)th
and first symbols of said slot.

9. A storage medium storing a program implementing a transmission diversity detection method for notifying presence or absence of a transmission diversity of spread spectrum communication by modulation of SCH (Synchronization channel), said program comprising:

calculating step for calculating a calculated value of $C_{2n,0} \times S_{2n,0}^* + C_{2n,0}^* \times S_{2n,0} + C_{2n,1} \times C_{2n,1}$, in first and second symbols in a predetermined number of series of slots with respect to a reception signal, taking a primary CPICH (Common pilot channel) symbol with respect to said first symbol as $C_{2n,0}$, a SCH symbol with respect to said first symbol as $S_{2n,0}$, a primary CPICH symbol with respect to said second symbol as $C_{2n,1}$ and a SCH symbol with respect to said second symbol as $S_{2n,1}$, and taking a complex

5 judging step for making judgment whether transmission
diversity is present or not depending upon positive or negative
of said calculated value.

deriving said complex conjugate $C_{2n,0}^*$ of said primary CPICH symbol $C_{2n,0}$, a complex conjugate $S_{2n,0}^*$ of SCH symbol $S_{2n,0}$, a complex conjugate $C_{2n,1}^*$ of said primary CPICH symbol $C_{2n,1}$ and a complex conjugate $S_{2n,1}^*$ of said SCH symbol $S_{2n,1}$;

said judging step makes judgment whether transmission diversity is performed or not depending upon positive or negative of sign of said sum.

11. A storage medium as set forth in claim 9, wherein said predetermined slot is even numbered slots in one frame, said first and second symbols are (0)th and first symbols of said slot.